

# PRODUCT OVERVIEW



## Group I

	SN 70	SN 100	SN 150	SN 500	SN 650	Brightstock
Kin. Visc. At 40 °C, cSt	12 - 15	17 - 21.5	29.1 - 34	88 - 102.5	145 - 155	470 - 690

## Group II

	110 N	150 N	230 N	600 N
Kin. Visc. At 40 °C, cSt	19.4 - 22	29 - 31	42.1 - 45.5	108 - 112

Fulfil the requirements of US FDA 21 CFR 178.3620 (b) and FDA 21 CFR 178.3570.

## Group III

	4 cSt	6 cSt	8 cSt
Kin. Visc. At 40 °C, cSt	18.9 - 21.95	32 - 37	43 - 45

## Group IV

	PAO 2 cSt	PAO 2.5 cSt	PAO 4 cSt	PAO 5 cSt	PAO 6 HVI	PAO 6 cSt	PAO 7 cSt	PAO 8 HVI	PAO 8 cSt	mPAO 65 cSt	mPAO 100 cSt	mPAO 150 cSt
Kin. Visc. At 40 °C, cSt	5.2	8.4	16.8	24.4	29.1	30.4	37.7	45.9	46.7	605	992	1719

## Group V / Specialties

Blown Oils  
Rubber Process Oils

Wax / Slack Wax  
Solvents

Re-refined Oils

Bio - Ester

Naphthenics

# PRODUCT OVERVIEW



## Low Viscosity

	PHC-2H	PHC-3	PHC-5A	PHC-5B	PHC-10A	PHC-10B
Kin. Visc. At 40 °C, cSt	2.1 - 2.8	3.2 - 3.6	4 - 5	4 - 5	8 -11	8 -11

## Process Oils

	PO 85	PO 100	PO 150	PO 500	PO 650	
Kin. Visc. At 40 °C, cSt	15 - 18	20.6 - 22.5	29.5 - 34.5	90 - 102.5	145 - 155	
	MP 100	MP 105	MP 150	MP 230	MP 340	MP 600
Kin. Visc. At 40 °C, cSt	17.5 - 19.5	19.6 - 21.9	28.5 - 31.5	42.3 - 45.0	65 - 75	108.5 - 111.5

MP Process Oils: Fulfil the requirements of US FDA 21 CFR 178.3620 (b) and FDA 21 CFR 178.3570.

## White Oils

	WO 80	WO 100	WO 350	WO 500
Kin. Visc. At 40 °C, cSt	14 - 17	19 - 23	65 - 75	85 - 100

**WO Line:** Fully the requirements of US FDA 21 CFR 178.3620 (a), European, British and US Pharmacopeia. Furthermore, the requirements of NSF H1, HX-1 and 3H.

Date: 12.08.2021